

EA32C-IN




Key Features



Usb Auto-Play

You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



Daisy Chain

The display can mirror the content (to another display) into its display port out coming from its display port in. This set up creates a daisy chain like structure allowing for monitors to be set up as Video Wall mode.



Display Control

Digital Signage Display SoC enables the users to control our displays using RS232 commands in a Local Area Network. Together with the full RS232 command list you can change/set volume, turn on/off the monitor, set a schedule for content display, set a webpage link to be displayed and give a wide range of commands in real-time.




Scheduler

Digital Signage Monitor Software allows many important features such as Scheduler. Scheduler sets your display turn on/off time easily and lets you not to worry about the status of your displays in any time.



Signal Failover

Our SoC Software has a protection for "No Signal" scenario. If the USB is unplugged after your content is set to be displayed with USB, the display will either show your customized banner or search for any other signal from other sources (HDMI, Display Port, etc.). This failover protection is constructed for higher user experience.



Pixel Shifting

The Pixel Shifting feature can be activated in order to reduce the potential risk of image sticking when static content is displayed over long periods of time. The feature periodically shifts the image on the display, without causing any interference of the visual experience.

Panel

Screen Size	32"	Panel Technology	FSA (VA)
Backlight Type	Direct-Type LED	Brightness (typical)	350 cd/m ²
Native Resolution	1920 x 1080 (16:9) - FHD	Contrast Ratio (typical)	3000:1
Dynamic Contrast Ratio	35000:1	Response Time (typical)	8.5 ms
Active Area (H x V)	698.40 x 392.85 mm	Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Color Value	16.7M (8bits)	Screen Treatment	3H
Haze Level	0,03	Refresh Rate	60 Hz
Orientation	Landscape	Operation Hours	16/7
Area of Usage	Indoor		

Built-in System

Mainboard Model	17MB130VS	Operating System	Linux (HTML5 based app support)
Wired	10/100 Mbps	WiFi	WiFi 4 (802.11 a/b/g/n)
Bluetooth	NA		

Monitor Connectivity

RGB Input	N/A	RGB Output	N/A
Video Input	1xHDMI2.0, 2xUSB2.0, DP1.2a	Video Output	DP1.2a
Audio Input	N/A	Audio Output	Headphone
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)	External Sensor	RJ12

Mechanical

Product Dimensions (WxDxH)	734 x 78 x 435 mm	Package Dimensions (WxDxH)	795 x 128 x 530 mm
Product Weight	TBD	Package Weight	TBD
Vesa Mounting	75 x 75 mm M4	Bezel Width	B:21 T/ L/R:14 mm

Power

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	------------------------------

Power Consumption

Typical	42 W	Maximum	65 W
Deep Standby	≤0.5 W		

Features

Mechanical Features	Joystick, IR Extender or Embedded IR Support Options, Rocker Switch, Detachable power cable(Class 2), Logo on bezel only horizontal	Speaker	2 x 6 W
---------------------	--	---------	---------

Certification

Safety	YES	EMC	YES
CE	YES		